



PERSPECTIVES™ STEEL SIDING

Introducing Perspectives by EDCO, a high-performance line of steel exterior solutions with a multi-position lock and integrated, concealed ventilation to achieve a seamless rainscreen assembly without additional components. Available in a thoughtfully curated collection of sophisticated solid colors and woodgrain finishes, Perspectives offers unmatched design flexibility and enhanced performance.

TECHNICAL DATA

SUBSTRATE	Roll-formed, CS Type B - 0.02" (nominal) thick G90 hot-dipped galvanized steel
APPLICATION	Wall, soffit
MINIMUM ULTIMATE TENSIL STRENGTH	Complies with ASTM A653
MINIMUM ULTIMATE YIELD STRENGTH	33,000-55,000 psi
MINIMUM ELONGATION	>20%
MODULUS OF ELASTICITY	30
COEFFICIENT OF LINEAR EXPANSION	6.7 u-in/in/°F
MELTING RANGE	2600°F
THICKNESS	0.02", 26 ga.
COATING	Woodgrain Finish: RealGrain™ Coating Technology Solid Color Finish: ENTEx® Coating Technology
FASTENING SYSTEM	Concealed
WARRANTY	RealGrain Coated: 20-yr Limited Warranty ENTEx Coated: 30-yr Limited Warranty



MATERIAL DATA

- 100% Recyclable
- Up to 80% Recycled Content
- VOC-Free
- Lead-Free

LEARN MORE AT [EDCOPRODUCTS.COM/PERSPECTIVES](https://edcoproducts.com/perspectives)



DIMENSIONS

PANEL LENGTH	12'
PANEL COVERAGE	4", 6"
PANEL DEPTH	0.75"
VENTILATION OPENINGS	0.156" x 0.375"
VENTILATION INTERVALS	1.375"
VENTILATION MAXIMUM	4" panel: 4.07 sq.in/Lft. 6" panel: 3.05 sq.in/Lft.
COURSE SPACING	0.1" (tight) 0.3" (nickel gap)



Design Without Limits with Perspectives by EDCO
 800.593.2680 | edcoproducts.com | © EDCO Products Inc.